



DAELIM DAYSTAR 125 / VT 125
SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

(1) Sideplates

- Loosen the two screws that secure the side supports of the rear fender, in its front part.
- Remove the two cap nuts that secure the side supports in its horizontal part.
- Push inward those screws. On the inside part, they are both welded to the ends of a plate, so you have to push both at the same time.
- The two side plates of the SPAAN sissybar must be placed between the rear fender and the frame, matching their holes with the place where the screws will pass through.
- Place the screws again through the side plates and secure the assembly with the nuts previously removed.
- Tighten the loosened screws in the first step.



(2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack TC, the luggage rack arch to the sideplates SPAAN with the four screws **M6x20**. Put **M6** nuts from the inside.

(3) Rack

For installation in luggage racks kits or in any sissybars of our brand SPAAN. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with 4 screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



(4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

