

HARLEY DAVIDSON SPORTSTER >2005 SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

(1) Sideplates

The sissybar is mounted on the chromed side supports that flank the rear fender.

Remove the original screws. Place the **Ø16x4XØ8** caps of kit, on the chrome side supports. Place the **SPAAN** support side plates on the caps. At the front part must be used the **M8x50** screws and **M8** nuts included in the kit. On the rear, put the original screws that have been removed from the front part, with the original threaded plates from the inside of the rear fender.



(2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

(3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



(4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

