



HARLEY DAVIDSON DYNA

SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

(1) Sideplates

The side plates are placed between the rear fender and frame.

Remove the front bezel screw (Torkx 45)

Remove the screw that secures the turn light. It runs from the inside of the fender to outward, threaded on turn light.

Separate slightly inward welded a plate which carries at its ends two bushes, which cross the fender, outwardly supported by the frame. Withdraw inwards, it allows placing the side plates in position. The front hole must match the position of the front and rear screw with the screw that secures the turn light.

Before this drill there is another, with a ripped to the bottom groove, whereby the turn light cable to be inserted.



(2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack TC, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

(3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the small arch or the sissybar uprights and fix the assembly with the 4 screws **M6x20** and nuts **M6** included in the original kit. **In all LUGGAGE RACKS is required to mount the luggage rack arch**, to give more rigidity to the assembly.



(4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

