

TRIUMPH ROCKET III

SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

(1) Sideplates

The sideplates of the sissy bar are placed on the chrome trims that are on either sides of the rear fender.

On the front - Remove the screws that secure the chromed trims. Place the sides plates of the kit, on the trims, placing the **20x8x8.5** bushings between the plates and the trims. Fix it with the **M8x60** screws and the nuts **M8** that are included in the kit.

At the rear - Place the **20x10x8.5** bushings between the trim and the side plate of the kit, and fix the assembly with the **M8x45** screws.



(2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

(3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



(4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

