

SPAAN

INDIAN CHEF CLASSIC 2014

SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS



The side plates are placed between the rear fender side skirts and fender.

Front - Remove the screws that secure the bezel. Place on the chassis of the bike a cap $\text{Ø}20 \times 10 \times \text{Ø}8.5$ from kit. Putting on the side plate and the back plate, the bezel. Secure the assembly with the screw **M8x30**.

Rear - Place on the chassis of the bike a cap $\text{Ø}20 \times 8 \times \text{Ø}8$ from kit. Putting on the side plate and the back plate, the bezel. Secure the assembly with the screw **M8x30**.



(1) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack TC, the luggage rack arch to the sideplates SPAAN with the four screws **M6x20**. Put **M6** nuts from the inside.

(2) Rack

For installation in luggage racks kits or in any sissybars of our brand SPAAN. We must place it the inside of the small arch or the sissybar uprights and fix the assembly with the 4 screws **M6x20** and nuts **M6** included in the original kit. **In all LUGGAGE RACKS is required to mount the luggage rack arch, to give more rigidity to the assembly.**



(3) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

