



HARLEY DAVIDSON STREET 750 XG

SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

(1) Sideplates

The SPAAN sissybar is placed on the side supports of the motorcycle that secure the rear fender.

At the front part. Remove the original screw. Place a $\varnothing 18 \times 6 \times \varnothing 10$ cap on the lateral of the bike. Place the front part of the side plate of the SPAAN sissybar on the cap. Secure the assembly with the M10x35 screw.

In the back part. Remove the original screw. Place a $\varnothing 16 \times 15 \times \varnothing 10$ cap on the lateral of the bike. Place the rear part of the side plate of the SPAAN sissybar on the cap. The assembly must be fixed with the M10x50 screw.



(2) Sissybar uprights–luggage rack arch

Install the sissybar upright (high or low), or in case of a luggage rack or luggage rack TC, the luggage rack arch to the sideplates SPAAN with the four screws M6x20. Put M6 nuts from the inside.



(3) Rack

For installation in luggage racks kits or in any sissybars of our brand SPAAN. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with 4 screws M6x20 and nuts M6 included in the kit. In all LUGGAGE RACKS is required to mount the small arch, to give more rigidity to the assembly.



(4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).



This Images can be different from current models.