

# SPAAN



## HARLEY DAVIDSON BREAKOUT FXSB SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

### (1) Sideplates

The SPAAN sissybar is placed on the side supports of the motorcycle that secure the rear fender.  
At the front part. Remove the original screw. Place a  $\varnothing 18 \times 6 \times \varnothing 10$  cap on the lateral of the bike. Place the front part of the side plate of the SPAAN sissybar on the cap. Secure the assembly with the  $3/8'' \times 30$  screw.

In the back part. Remove the original screw. Place a  $\varnothing 18 \times 6 \times \varnothing 10$  cap on the lateral of the bike. Place the rear part of the side plate of the SPAAN sissybar on the cap. The assembly must be fixed with the  $3/8'' \times 30$  screw.



### (2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack TC, the luggage rack arch to the sideplates SPAAN with the four screws **M6x20**. Put **M6** nuts from the inside.

### (3) Rack

For installation in luggage racks kits or in any sissybars of our brand SPAAN. We must place it the inside of the small arch or the sissybar uprights and fix the assembly with the 4 screws **M6x20** and nuts **M6** included in the original kit. **In all LUGGAGE RACKS is required to mount the luggage rack arch**, to give more rigidity to the assembly.



### (4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

