

## ROYAL ENFIELD CLASSIC

### SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

#### (1) Sideplates

The side plates of the **SPAAN** sissy bar must be fixed in the passenger seat, on the same anchoring where the original handle is attached.

To mount the sissy bar, the original handle must be removed. Into its place, put the side plates of the sissy bar, placing the  $\varnothing 20 \times 4 \times \varnothing 8.5$  spacer bushings, included in the kit, between the side plates and the seat. the original screws must be used to secure the side plates.



#### (2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

#### (3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



#### (4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

