

## HARLEY DAVIDSON ROADSTER XL1200 SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

### (1) Sideplates

The anchor side plates of the **SPAAN** sissybar are placed between the fender and the outer support where the fender is fixed. Remove the original screw marked with the letter "A" in the image 1. **(Torx 40, nut 13 inside)**

Remove the screws "B" and "C" that go by the inner side of the fender and fix the flash signal. **(Hexagonal 13)**

Enter the side plate of the sissybar between the fender and external support by aligning their holes with the position of the screws. the side plates should be placed so that the folding is facing the outwards by its top part. Fix the assembly using the original "A" and "B" screws. The "C" screw will be replaced by the **5/16"x35** screw included in the kit.



### (2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

### (3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



### (4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

