



# INDIAN SCOUT / SCOUT SIXTY

## SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

#### (1) Sideplates

Remove the four screws on both sides of the rear fender. (Do not remove the four screws at the same time to prevent the fender drop from the bike). Place the side plates of the **SPAAN** sissybar by matching the two largest holes of the side plates with the screw anchors that we removed at first. Place the **Ø20x6** bushings in the front part and the **Ø20x8** bushings in the rear part between the side plates and the fender. Fix the sides plates with the **M8x25** screws that are included in the kit.

.





### (2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack TC, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

#### (3) Rack

For installation in luggage racks kits or in any sissybars of our brand SPAAN. We must place it the inside of the small arch or the sissybar uprights and fix the assembly with the 4 screws M6x20 and nuts M6 included in the original kit. In all LUGGAGE RACKS is required to mount the luggage rack arch, to give more rigidity to the assembly.





### (4) **Pad**

Join the set with four screws M5x10 that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).



