

## HYOSUNG AQUILA GV 125S/300S BOBBER SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

### (1) Sideplates

The **SPAAN** sissybar is placed on the side supports of the motorcycle that secure the rear fender.

Place the side plates of the sissybar, placing the  $\varnothing 20 \times 13$  bushings in front part and  $\varnothing 20 \times 30$  bushings in the rear part (both included in the kit) between the plates and the motorcycle. The **M8x80** screws must be used in front and **M8x70** in rear. Use the original nuts to fix the assembly.



### (2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

### (3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



### (4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

