



SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

(1) Sideplates

Remove the trims on both sides of the rear fender and then the inner plates. Place the side plate of the SPAAN sissybar and then put the plate of the trim, inserting a $\varnothing 14 \times 4 \times 8.5$ bushing between them, securing it with screws **M8x40** included in the kit and the original nuts. Finally install the original trim. **Important!** exchange the position of the inner plates: right plate (**R**) must be installed on the left side; and left plate (**L**) on the right side. (images 1 y 2).



(2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

(3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



(4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

