



KEEWAY V-CRUISE 125/ V302C/ BD125 / BD300  
BENDA FOX 125 / 300 / Chinchilla 125-300  
Romet Benda Chinchilla 125/300  
SISSYBAR / LUGGAGE RACKS MOUNTING INSTRUCTIONS

### (1) Sideplates

The SPAAN backrest side plates fit on the rear fender trims. Remove the original screws. Place a rubber washer at the front between the side plate and the chassis and fix them with the **M10x50** screw and the **M10** washer. On the rear part, place a rubber washer and then the **20x6x10** bushing and fix them with the **M10x50** screw, **M10** washer and self-locking nut included in the kit.



### (2) Sissybar uprights – luggage rack arch

Fix the sissybar upright (high or low), or in case of a luggage rack or luggage rack **TC**, the luggage rack arch to the sideplates **SPAAN** with the four screws **M6x20**. Put **M6** nuts from the inside.

### (3) Rack

For installation in luggage racks kits or in any sissybars of our brand **SPAAN**. We must place it the inside of the sissybar uprights or the small arch and fix the assembly with **4** screws **M6x20** and nuts **M6** included in the kit. **In all LUGGAGE RACKS is required to mount the small arch**, to give more rigidity to the assembly.



### (4) Pad

Join the set with four screws **M5x10** that accompany the kit. (In the back of the pad is marked with four holes in the fabric the position of the threads).

